

ABSENT ESSENTIAL

ID 41

ABSENT ESSENTIAL represents a **high-quality, essential** and **efficient back-lighting** solution for offices or public spaces. Suitable for recessed, ceiling or suspended installation, ABSENT ESSENTIAL comes in different dimensions that make it versatile in every context.

☑ Features

- Direct emission
- UGR<19
- IP 40

💡 Led

- 3000K/4000K
- >115 lm/W
- CRI >94
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- DPL technology for controlled emission UGR<19

📦 Body

- Aluminum with epoxy powder coating

☆ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency C
- 5 years warranty

📦 On request


- DALI - code D
- Bluetooth - code BT*
- Emergency 1 hr - code EM*
- Emergency 3 hrs - code EM3H*
- False ceiling version 625x625mm*

* Where available



ABSENT ESSENTIAL DPL

Diffuser with Diamond Prism LED (DPL) technology for controlled emission UGR<19.



Cod. 4000K	Led	lm	Lmm
4IDPL18K4E	18W	1750	295x295
4IDPL36K4E	36W	4140	595x595
4IDPL22K4EM3	22W	2150	595x295
4IDPL36K4EM3	36W	4140	1195x295
4IDPL60K4EM6	60W	7150	1195x595
4IDPL58K4EM3	58W	6670	1495x295

Cod. 3000K	Led	lm	Lmm
4IDPL18K3E	18W	1610	295x295
4IDPL36K3E	36W	3809	595x595
4IDPL22K3EM3	22W	1978	595x295
4IDPL36K3EM3	36W	3809	1195x295
4IDPL60K3EM6	60W	6578	1195x595
4IDPL58K3EM3	58W	6136	1495x295

ACCESSORIES




Plasterboard installation kit.

41AA17E



Adjustable suspension kit.
Cable length 3000mm.

41AA1330E



Ceiling installation kit.

41AAE300300
41AAE600600
41AAE600300
41AAE1200300
41AAE1200600
41AAE1500300



3-5 poles ceiling power supply box.
Cable length 2000mm.

00AA16
00AA165P