

BEN IP54

ID 10

BEN is a universal appliance for wall, ceiling, suspension or recessed installation for exteriors with **bodies entirely made of aluminium, without welds**. The **IP54** version is proposed with **impact-resistant satin diffuser**, housed in a circular aluminium frame with sealing gasket. **The mid-power LEDs on the circular board avoid the creation of shadow zones** and are connected to the internal supports through quick connectors, for easy electrification.

☑ Features

- Direct emission
- IP 44 suspended
- IP 54

💡 Led

- 3000K/4000K
- >125 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B20 >80.000h

🕒 Specifications

- Built-in driver
- Impact resistant satin acrylic diffuser with perimeter screen printing and homogeneous emission with UGR<22
- Circular aluminum frame with sealing gasket

📦 Body

- Aluminum with epoxy powder coating

🎨 Colors

- Matte white RAL 9003 - code B

★ Certifications

- CE Conformity
- Energy efficiency C
- 5 years warranty

⇄ Related products

- Ben suspended/ceiling (p.114)
- Ben recessed (p.155)

📄 On request


- DALI - code D*
- Bluetooth - code BT*
- Emergency 1 hr - code EM*
- Emergency 3 hrs - code EM3H*
- 2700K - code K27*

* Where available



BEN IP54 SMALL

Impact resistant satin-acrylic diffuser with perimeter screen printing, UGR<22.




IP 44 SUSPENDED
IP 54

| Cod. 4000K | Led | lm | Ømm |
|------------|-----|------|-----|
| 10PG6K454 | 6W | 798 | 257 |
| 10PG12K454 | 12W | 1598 | 257 |
| 10PG18K454 | 18W | 2394 | 257 |

| Cod. 3000K | Led | lm | Ømm |
|------------|-----|------|-----|
| 10PG6K354 | 6W | 742 | 257 |
| 10PG12K354 | 12W | 1486 | 257 |
| 10PG18K354 | 18W | 2226 | 257 |

BEN IP54 MEDIUM

Impact resistant satin-acrylic diffuser with perimeter screen printing, UGR<22.




IP 44 SUSPENDED
IP 54

| Cod. 4000K | Led | lm | Ømm |
|------------|-----|------|-----|
| 10PG15K454 | 15W | 2111 | 397 |
| 10PG21K454 | 21W | 2887 | 397 |

| Cod. 3000K | Led | lm | Ømm |
|------------|-----|------|-----|
| 10PG15K354 | 15W | 1963 | 397 |
| 10PG21K354 | 21W | 2684 | 397 |

BEN IP54 LARGE

Impact resistant satin-acrylic diffuser with perimeter screen printing, UGR<22.



IP 44 SUSPENDED
IP 54

| Cod. 4000K | Led | lm | Ømm |
|------------|-----|-------|-----|
| 10PG58K454 | 58W | 8072 | 620 |
| 10PG96K454 | 96W | 12710 | 620 |

| Cod. 3000K | Led | lm | Ømm |
|------------|-----|-------|-----|
| 10PG58K354 | 58W | 7507 | 620 |
| 10PG96K354 | 96W | 11820 | 620 |

ACCESSORIES



Single wire adjustable suspension kit. Cable length 1500/3000mm.

10AA13
10AA1330



3-5 poles ceiling power supply box. Cable length 2000mm.

00AA16
00AA165P



Kit for recessed installation.

10AA19S - BEN SMALL
10AA19M - BEN MEDIUM
10AA19L - BEN LARGE