

FLEX STRIP LED

ID 83

Our range of **FLEX STRIP LED**, flexible and adhesive, is available in a wide choice of color temperatures: Tunable White, Dim to Warm or RGBW. Sectionable every 50mm, the strips are compatible with high quality drivers and controllers for effective light management.

☑ Features

- IP 20; IP 65

💡 Led

- 2700K/3000K/4000K/
5000K/TW/RGBW/DTW
- >100 lm/W
- CRI>90
- Eye safety: RG0
- Mac Adams 3
- L80/B10 >50.000h

☆ Certifications

- CE Conformity
- Energy efficiency F
- 5 years warranty



STRIP LED _____ IP 20

Adhesive LED strip 24V CRI>90.

Length: 5000mm - sectionable every 50mm.



Cod. 2700K	Led	lm/m	mm
83SL10K27	10W/m	818	5000
83SL15K27	15W/m	1228	5000
83SL20K27	20W/m	1637	5000
83SL24K27	24W/m	2009	5000

Cod. 3000K	Led	lm/m	mm
83SL10K3	10W/m	880	5000
83SL15K3	15W/m	1320	5000
83SL20K3	20W/m	1760	5000
83SL24K3	24W/m	2160	5000

Cod. 4000K	Led	lm/m	mm
83SL10K4	10W/m	941	5000
83SL15K4	15W/m	1412	5000
83SL20K4	20W/m	1883	5000
83SL24K4	24W/m	2311	5000

STRIP LED _____ IP 65

Adhesive LED strip 24V CRI>90.

Length: 5000mm - sectionable every 50mm.

Cod. 2700K	Led	lm/m	mm
83SL10K27IP65	10W/m	735	5000
83SL15K27IP65	15W/m	1023	5000

Cod. 3000K	Led	lm/m	mm
83SL10K3IP65	10W/m	790	5000
83SL15K3IP65	15W/m	1100	5000

Cod. 4000K	Led	lm/m	mm
83SL10K4IP65	10W/m	845	5000
83SL15K4IP65	15W/m	1177	5000

Cod. 5000K	Led	lm/m	mm
83SL10K5IP65	10W/m	904	5000
83SL15K5IP65	15W/m	1259	5000

STRIP LED _____ TUNABLE WHITE

Cod. 2700/6500K	Led	lm/m	mm
83SL24TW	24W/m	2240	5000

STRIP LED _____ DIM TO WARM

Cod. 1800/3000K	Led	lm/m	mm
83SL24DTW	24W/m	2160	5000

STRIP LED _____ RGBW

Cod.	Led	lm/m	mm
83SL17RGW	17W/m	1170	5000

STRIP LED _____ RGBW IP65

Cod.	Led	lm/m	mm
83SL17RGWIP65	17W/m	1050	5000

DRIVER

Driver to be selected according to the power and length of the installed LED strip.

IP 20

INDEPENDENT INSTALLATION CONVERTER (IS) - ON/OFF

Cod.	Led
83LC6024IS	24V 60W
83LC12024IS	24V 120W
83LC20024IS	24V 200W

Compatible products: PROFREEL - ENDO

INDEPENDENT INSTALLATION CONVERTER (IS) - DALI

Cod.	Led
83LC6024ISD	24V 60W
83LC10024ISD	24V 100W
83LC15024ISD	24V 150W

Compatible products: PROFREEL - ENDO

INDEPENDENT INSTALLATION CONVERTER SLIM - ON/OFF

Cod.	Led
83LC6024SIS	24V 60W
83LC10024SIS	24V 100W

Compatible products: PROFREEL SLIM DISPLAY

LINEAR CONVERTER 30x21mm - ON/OFF

Cod.	Led
83LC6024	24V 60W
83LC10024	24V 100W

Compatible products: PROFREEL

REMOTE INSTALLATION

HOUSED INSIDE THE PROFILE



IS

SLIM

LINEAR

INDEPENDENT INSTALLATION CONVERTER (IS) - BLUETOOTH

Cod.	Led
83LC6024ISBT	24V 60W
83LC10024ISBT	24V 100W
83LC15024ISBT	24V 150W

Compatible products: PROFREEL - ENDO

INDEPENDENT INSTALLATION CONVERTER SLIM - DALI

Cod.	Led
83LC7024SISD	24V 70W
83LC12024SISD	24V 120W

Compatible products: PROFREEL SLIM DISPLAY

LINEAR CONVERTER 30x21mm - DALI

Cod.	Led
83LC6024D	24V 60W
83LC10024D	24V 100W

Compatible products: PROFREEL

CONTROLLER BASIC

Cod.	Note
DIMKITTW	Tunable White + Remote



Cod.	Note
DIMKITRGBW	RGBW + Remote



CONTROLLER DALI RGBW/TW

Cod.	Note
83CL4XID	DALI RGBW/Tunable White



ACCESSORIES



Start-of-line connector IP 20.

83AA09EL

IP 20/Dim to warm

83AA09ELRGB

RGBW

83AA09ELTW

Tunable white



Start-of-line connector IP 65.

83AA09ELIP

IP 65

83AA09ELIPRGB

RGBW IP 65



Strip-Strip linear junction IP 20.

83AA11SL

IP 20/Dim to warm

83AA11RGB

RGBW

83AA11TW

Tunable white



Strip-Strip linear junction IP 65.

83AA11IP

IP 65

83AA11IPRGB

RGBW IP 65



Wired linear junction IP 20.

83AA11CC150

IP 20/Dim to Warm

83AA11CC150RGB

RGBW

83AA11CC150TW

Tunable white



Wired linear junction IP 65.

83AA11CC150IP

IP 65

83AA11CC150IPRGB

RGBW IP 65