

**FLIP** is the new and **revolutionary lighting method for spaces with 24mm visible structure suspended ceilings**. The ultra-slim linear luminaire can be arranged as desired to create light patterns, allowing designers greater creative freedom in respect to standard panels. **Controlled direct emission** ensures a low glare index (**UGR<16**) making FLIP ideal for both office lighting and general spaces. The lateral emission ensures that the luminaire uses the false ceiling as a reflective surface, to maximize visual comfort, it is **also available in PG version**, for those environments where diffused lighting is needed. **FLIP: free your creativity.**

#### ☑ Features

- Direct emission
- UGR<16; <22
- IP 40

#### 💡 Led

- 3000K/4000K
- >125 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

#### 🕒 Specifications

- Polycarbonate lens with ILC (Indirect Light Control) emission to favor indirect illumination, UGR<16
- PG diffuser for homogeneous emission, with UGR<22

#### ☆ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency F
- 5 years warranty

#### 📦 On request

- DALI - code D
- Bluetooth - code BT\*
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H\*


\* Where available





# FLIP\_\_\_\_\_

Polycarbonate lens with ILC (Indirect Light Control) emission to favor indirect lighting, UGR<16.



IP 40

Cod. 4000K	Led	lm	Lmm
42PC9K4	9W	1026	599


Cod. 3000K	Led	lm	Lmm
42PC9K3	9W	995	599



RECESSED

# FLIP\_\_\_\_\_PG

PG lens in frosted polycarbonate. UGR<22.



IP 40

Cod. 4000K	Led	lm	Lmm
42PO9K4	9W	1020	599

Cod. 3000K	Led	lm	Lmm
42PO9K3	9W	989	599



## ACCESSORIES



Straight electrified connector.

**42AA11EL**



2 ways 90° electrified connector.

**42AA05EL**



3 ways electrified connector.

**42AA06EL**



4 ways electrified connector.

**42AA07EL**



Driver 24V 35W for 1 fixture.

**42LC1X**



Driver 24V 35W for 1 fixture, DALI version.

**42LC1XD**



Driver 24V 60W up to 4 fixtures.

**42LC4X**



Driver 24V 60W up to 4 fixtures, DALI version.

**42LC4XD**



Driver 24V 100W up to 10 fixtures.

**42LC10X**



Driver 24V 100W up to 10 fixtures, DALI version.

**42LC10XD**



Kit for installation on plasterboard or semi-recessed panels.

**42AA14**

## TECHNICAL NOTES



*Thanks to the electrified connector and the side clips, installation to the false ceiling structure is immediate.*