GLEIS

GLEIS is the adjustable direct-indirect emission outdoor wall luminaire. Thanks to two rotating elements, perfectly integrated within its body and the high-performance concentrating optics, the light flux can be flexibly oriented to create different light effects. With an extremely compact body and a modern and minimal design available in different colors, GLEIS integrates perfectly into any environment. From Wall Washer to spotlight with a touch: GLEIS is the perfect solution to flexibly illuminate walls and passageways in outdoor environments at the same time.

☑ Features

- Direct/indirect emission
- IP 66

🖻 Led

- 3000K/4000K
- >100lm/W
- CRI>90
- Eye safety: RGO
- Mac Adams 3
 L80/B10 >50.000h

⊘ Specifications

- Built-in driver Adjustable concentrating
- optics and independent with UGR<22

Body Aluminum with epoxy

powder coating

C Colors

- White RAL 9003 wrinkled code W
- Black RAL 9005 wrinkled code BK
- Anthracite grey code GA
- Corten bronze code BC

☆ Certifications

- CE Conformity
- Energy efficiency F
- 5 years warranty

🗄 On request

- DALI code D
- Bluetooth code BT*

* Where available





GLEIS

Concentrating optics for direct and indirect emission, independent and rotating (90°).



IP 66

Cod. 4000K	Led	lm	mm	Cod
61D112K4	12W	1068	340	61
61DI24K4	24W	2136	620	61
61DI36K4	36W	3204	900	61[
61DI48K4	48W	4272	1180	61[
61DI60K4	60W	5340	1463	61[

Cod. 3000K	Led	lm	mm	
61DI12K3	12W	950	340	
61DI24K3	24W	1901	620	
61DI36K3	36W	2851	900	
61DI48K3	48W	3802	1180	
61DI60K3	60W	4752	1463	

TECHNICAL NOTES

ROTATING ELEMENTS ADJUSTMENT

The concentrating optics, mounted on rotating elements, allow the luminous flux to be directed independently by 90 degrees towards the wall - for a Wall Washer effect - or towards the outside - with a spotlight function - to illuminate walls, paths or areas at the same time passing.

