

HALL LED ESSENTIAL CEILING

ID 28

The cylindrical shape and the front cut-off give **HALL LED ESSENTIAL CEILING** a **modern look and optimize the light distribution** in a homogeneous way. Characterized by a pure and essential shape, it is ideal for residential and hospitality applications.

☑ Features

- Direct emission
- UGR<22
- IP 44

💡 Led

- 3000K/4000K
- >119 lm/W
- CRI>90
- Eye safety: RG0/RGI
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- Built-in driver
- SMD LED technology
- Opal polycarbonate diffuser

📦 Body

- Polycarbonate, with aluminum heat sink

🎨 Colors

- Matte white RAL 9003 - code B
- Matte black RAL 9005 - code C8

★ Certifications

- CE Conformity
- Energy efficiency E
- 5 years warranty

📄 On request


- DALI - code D
- Bluetooth - code BT*
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H*

* Where available



HALL LED ESSENTIAL CEILING

Opal polycarbonate diffuser.
 Beam angles: 90°. Cut-off>10°.



IP 44

Cod. 4000K	Led	lm	Ømm
28PGI5K4	15W	1779	204
28PG21K4	21W	2490	204

Cod. 3000K	Led	lm	Ømm
28PGI5K3	15W	1757	204
28PG21K3	21W	2402	204

DOWNLIGHT