

# ISI LED IP55

ID 31

**ISI LED IP55** is designed for **sterile environments**: a universal LED technology fixture for **false ceiling with visible and hidden structure**.

## ☑ Features

- Direct emission
- UGR<19; <22
- IP 55

## 💡 Led

- 3000K/4000K
- >106 lm/W
- CRI>90
- Eye safety: RGO/RGI
- Mac Adams 3
- L80/B10 >50.000h

## 🕒 Specifications

- Built-in driver
- Fixed power current driver
- Nominal life span 50.000h
- (T° max 50° C/failure rate ≤0.2% per 1,000h)
- Quick connector supplied as standard
- DPL with internal microprismatic plate, UGR<19
- PG with PMMA diffuser for homogeneous emission, UGR<22

## ☐ Body

- Extruded aluminum frame
- Steel sheet with epoxy powder coating

## 🎨 Colors

- White RAL 9003

## ☆ Certifications

- CE Conformity
- Energy efficiency D
- 5 years warranty

## 📦 On request

- DALI - code D
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H\*
- 5000K - code K5\*
- Ceiling version\*
- False ceiling version 625x625mm\*

\* Where available



## ISI LED IP55      DPL

DPL technology with UGR<19 composed by a microprismatic internal sheet.



Cod. 4000K	Led	Im	Lmm
3IDPL38K455	38W	3357	597x597
3IDPL64K455	64W	6547	597x597
3IDPL38K455M3	38W	3357	297x1197
3IDPL64K455M3	64W	6547	297x1197

Cod. 3000K	Led	Im	Lmm
3IDPL38K355	38W	3181	597x597
3IDPL64K355	64W	5952	597x597
3IDPL38K355M3	38W	3181	297x1197
3IDPL64K355M3	64W	5952	297x1197

## ISI LED IP55      PG

PMMA diffuser for homogeneous emission, UGR<22.



Cod. 4000K	Led	Im	Lmm
3IPG38K455	38W	3428	597x597
3IPG64K455	64W	6845	597x597
3IPG38K455M3	38W	3428	297x1197
3IPG64K455M3	64W	6845	297x1197

Cod. 3000K	Led	Im	Lmm
3IPG38K355	38W	3251	597x597
3IPG64K355	64W	6250	597x597
3IPG38K355M3	38W	3251	297x1197
3IPG64K355M3	64W	6250	297x1197

## ACCESSORIES



Kit of fixing brackets for installation on plasterboard, with hidden structure and on slats.

**KSFIP65**