

Thanks to a refined combination of materials and light emission **KERÌ gives originality to the cylinder**, the traditional shape of architectural outdoor lighting. The efficient lighting source offers a delicate indirect emission thanks to a reflector that collects the light and spread it through a satin glass. It is possible to **combined this smooth indirect light** with a **defined direct beam** thanks to a split on the base which also frees the downlight core for new vibrant lights. As **ceiling, wall and pendant light, KERÌ** is available in **two different sizes** with a modern decorative shade that gives personality to further play of light.

☑ Features

- Direct emission
- Direct/indirect emission
- IP 65
- IK 06

💡 Led

- 3000K/4000K
- >125 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- LED CoB technology
- Built-in driver

📏 Body

- Die-cast aluminum

🎨 Colors

- White RAL 9003 wrinkled - code W
- Black RAL 9005 wrinkled - code BK

☆ Certifications

- CE Conformity
- Energy efficiency E
- 5 years warranty

📦 On request

- DALI - code D*
- 2700K - code K27*
- 5000K - code K5*
- MINI version: Ø 60mm*


* Where available





KERÌ MINI IN

Indirect emission with glass diffuser.



IP 65


Cod. 4000K	Led	lm	Ømm
60IN6VOK4MN	6W 15°	441	60
60IN9VOK4MN	9W 15°	662	60



Cod. 3000K	Led	lm	Ømm
60IN6VOK3MN	6W 15°	412	60
60IN9VOK3MN	9W 15°	619	60

KERÌ SMALL IN

Indirect emission with glass diffuser.



IP 65


Cod. 4000K	Led	lm	Ømm
60INI2VOK4S	12W 15°	1066	80
60INI7VOK4S	17W 15°	1466	80



Cod. 3000K	Led	lm	Ømm
60INI2VOK3S	12W 15°	996	80
60INI7VOK3S	17W 15°	1370	80

KERÌ MINI DI

Direct/indirect emission with glass diffuser.



IP 65




Cod. 4000K	Led	lm	Ømm
60DI6VOK4MN	6W 15°	441	60
60DI9VOK4MN	9W 15°	662	60

Cod. 3000K	Led	lm	Ømm
60DI6VOK3MN	6W 15°	412	60
60DI9VOK3MN	9W 15°	619	60

KERÌ SMALL DI

Direct/indirect emission with glass diffuser.



IP 65



Cod. 4000K	Led	lm	Ømm
60DI12VOK4S	12W 15°	1066	80
60DI17VOK4S	17W 15°	1466	80

Cod. 3000K	Led	lm	Ømm
60DI12VOK3S	12W 15°	996	80
60DI17VOK3S	17W 15°	1370	80

ACCESSORIES



Ceiling kit for suspended installation with 5 pole power rose and 3000mm cable.

60AA165PMN



IP65 ceiling kit for suspended installation with 5 pole power rose and 3000mm cable.

60AA165PMNIP



Decorative reflector
 ø 300mm for MINI and
 ø 400mm for SMALL.
 Available colours:
 grey/white/black,
 special colors on request.

60AA300G
60AA300W
60AA300BK
60AA400G
60AA400W
60AA400BK



Wall installation kit.

60AA15MN
60AA15S

TECHNICAL NOTES

Indirect emission through the glass can be enhanced by direct emission from the spot.

