

# LINEA IP54

ID 12

**LINEA IP54** is the family of fixtures that combine **efficiency and energy saving** with a long life time. Ideal for **laboratories, walking areas and industrial environments**.

## ☑ Features

- Direct emission
- UGR<22
- IP 54
- IK 10
- -25°/+35°

## 💡 Led

- 3000K/4000K
- >98 lm/W; >103 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

## 🕒 Specifications

- Built-in driver
- Impact resistant polycarbonate diffuser

## 📦 Body

- Polycarbonate with high mechanical resistance
- Polyurethane foam seal (PUR)

## ☆ Certifications

- CE Conformity
- Energy efficiency D
- 5 years warranty

## 📄 On request


- DALI - code D
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H\*
- 5000K - code K5\*
- 6500K - code K65\*

\* Where available



## LINEA IP54 LONG

Impact resistant polycarbonate diffuser.




IP 54 IK10

Cod. 4000K	Led	lm	Lmm
12PO21K454	21W	2130	109x1160
12PO25K454	25W	2716	109x1160
12PO33K454	33W	3506	109x1160
12PO39K454	39W	3971	159x1160
12PO48K454	48W	4948	159x1160
12PO65K454	65W	6705	159x1160

Cod. 3000K	Led	lm	Lmm
12PO21K354	21W	1894	109x1160
12PO25K354	25W	2255	109x1160
12PO33K354	33W	2977	109x1160
12PO39K354	39W	3518	159x1160
12PO48K354	48W	4330	159x1160
12PO65K354	65W	5864	159x1160

## LINEA IP54 ROUND

Impact resistant polycarbonate diffuser.



IP 54 IK10

Cod. 4000K	Led	lm	Ømm
12PO10K454R	10W	1116	300
12PO13K454R	13W	1395	300
12PO18K454R	18W	1897	300
12PO27K454R	27W	2725	300

Cod. 3000K	Led	lm	Ømm
12PO10K354R	10W	911	300
12PO13K354R	13W	1185	300
12PO18K354R	18W	1641	300
12PO27K354R	27W	2461	300

# LINEA IP54 ROUND INTELLIGENT

Impact resistant polycarbonate diffuser. Integrated presence sensor, settable with deepswitch.



UGR<22

IP 54 IK10

Cod. 4000K	Led	lm	Ømm
12PO10K454RS	10W	1116	300
12PO13K454RS	13W	1395	300

Cod. 3000K	Led	lm	Ømm
12PO10K354RS	10W	911	300
12PO13K354RS	13W	1185	300