

LITE is the recessed installation luminaire characterized by its **minimal design and compact section**. The power supply electronics are integrated inside the body, while the closed optical system is protected against dust and accidental damage during installation. **The high-efficiency LED modules** ensure an elevated homogeneity without precluding light output.

☑ Features

- Direct emission
- UGR<19; <22
- IP 40

💡 Led

- 3000K/4000K
- >105 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- Built-in driver
- MP technology for controlled UGR, with UGR<19
- PG diffuser for homogeneous emission, with UGR<22

☐ Body

- Aluminum with epoxy powder coating

☆ Certifications

- CE Conformity
- Energy efficiency E
- 5 years warranty

⇄ Related products

- Lite suspended/ceiling (p. 139)

📦 On request


- DALI - code D
- Bluetooth - code BT*
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H*
- 5000K - code K5*
- False ceiling version 625x625mm*

* Where available



LITE MP RECESSED

Microprismatic diffuser with UGR<19.



UGR<19

IP 40





For recessed installation on false ceiling with visible structure.

Cod. 4000K	Led	lm	Lmm
47MP52K4R	52W	5304	596
47MP64K4R	64W	6528	596

Cod. 3000K	Led	lm	Lmm
47MP52K3R	52W	4925	596
47MP64K3R	64W	6135	596

LITE PG RECESSED

Methacrylate plate painted with opaline antistatic treatment for soft diffusing light emission, UGR<22.



UGR<22

IP 40




For recessed installation on false ceiling with visible structure.

Cod. 4000K	Led	lm	Lmm
47PG52K4R	52W	5460	596
47PG64K4R	64W	6720	596

Cod. 3000K	Led	lm	Lmm
47PG52K3R	52W	5132	596
47PG64K3R	64W	6316	596

LITE___MP LONG RECESSED

Microprismatic diffuser with UGR<19.



IP 40


For recessed installation on false ceiling with visible structure.

Cod. 4000K	Led	lm	Lmm
47MP52K4M3V	52W	5304	1196
47MP64K4M3V	64W	6528	1196

Cod. 3000K	Led	lm	Lmm
47MP52K3M3V	52W	4925	1196
47MP64K3M3V	64W	6135	1196

LITE___PG LONG RECESSED

Methacrylate plate painted with opaline antistatic treatment for soft diffusing light emission, UGR<22.



IP 40

For recessed installation on false ceiling with visible structure.

Cod. 4000K	Led	lm	Lmm
47PG52K4M3V	52W	5460	1196
47PG64K4M3V	64W	6720	1196

Cod. 3000K	Led	lm	Lmm
47PG52K3M3V	52W	5132	1196
47PG64K3M3V	64W	6316	1196