

LUDO LINEAR 2.0

ID 20

LUDO LINEAR 2.0 is the linear luminaire for low voltage tracks, **dimmable and equipped with PG optics for homogeneous emission (UGR<22) or CLD collimated optics with controlled emission (UGR<16)**. Thanks to the quick fixing, LUDO LINEAR 2.0 is extremely versatile and becomes ideal for the retail world or contemporary living areas.

☑ Features

- Direct emission
- UGR<16; <22
- IP 40

💡 Led

- 3000K/4000K
- >120 lm/W
- CRI>90
- Eye safety: RG0/RGI
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- 48V DC operation
- SMD LED technology
- PG diffuser in satin methacrylate for homogeneous emission (UGR<22)
- Diffuser with CLD collimated optics (UGR<16)

📏 Body

- Anodized aluminum

🎨 Colors

- White RAL 9003 - code B
- Black RAL 9011 - code C8

🌟 Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency D
- 5 years warranty

⇄ Related products

- LV Track (p. 216)

📦 On request

- DALI - code D*
- Bluetooth - code BT*


** Where available*

*For SWITCHDIM command
use DIMTDS (p. 38!)*



LUDO LINEAR 2.0 PG

PG diffuser in satin-finished methacrylate for homogeneous emission, UGR<22.



IP 40




Cod. 4000K	Led	lm	Lmm
20PG6K4	6W	708	365
20PG12K4	12W	1416	725
20PG18K4	18W	2124	1085

Cod. 3000K	Led	lm	Lmm
20PG6K3	6W	649	365
20PG12K3	12W	1298	725
20PG18K3	18W	1947	1085

LUDO LINEAR 2.0 CLD

Direct emission with CLD technology, with collimated diffuser, UGR<16.



IP 40



Cod. 4000K	Led	lm	Lmm
20CLD6K4	6W	616	365
20CLD12K4	12W	1232	725
20CLD18K4	18W	1848	1085

Cod. 3000K	Led	lm	Lmm
20CLD6K3	6W	565	365
20CLD12K3	12W	1129	725
20CLD18K3	18W	1694	1085