

OVVIO DISPLAY LED

ID 40

OVVIO DISPLAY LED is the recessed luminaire for plasterboard ceilings with a **compact design** and a **framebit of 4mm**. Fastening system and quick electrical connection facilitate the installation. Low and high power LED modules allow to always find the best lighting solution. The maximum length of the profiles is over three metres, with a 280mm modularity and corner elements for wall or ceiling mount.

☑ Features

- Direct emission
- UGR<22
- IP 40

💡 Led

- 3000K/4000K
- >98 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B20 >80.000h

🕒 Specifications

- Built-in driver
- Diffuser in extruded PMMA for soft emission without shadow areas

📏 Body

- Aluminum with epoxy powder coating

🎨 Colors

- Matte white RAL 9003 - code B
- Matte black RAL 9005 - code C8

★ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency C
- 5 years warranty

📦 On request


- DALI - code D
- Bluetooth - code BT*
- Emergency 1 hr - code EM*
- Emergency 3 hrs - code EM3H*
- 2700K - code K27*
- 5000K - code K5*
- Human Centric Lighting*

* Where available



OVVIO DISPLAY LED

Diffuser in extruded PMMA (UGR<22) for soft emission without shadow areas.



← 56 →



50 x L + 1 mm



UGR<22

IP 40



End caps not included.

LOW POWER VERSION (20 W/m)

Cod. 4000K	Led	lm	Lmm
40PG18K4	18W	1770	844
40PG24K4	24W	2360	1124
40PG30K4	30W	2951	1404
40PG36K4	36W	3540	1684
40PG42K4	42W	4130	1964
40PG48K4	48W	4721	2244
40PG54K4	54W	5310	2524
40PG60K4	60W	5900	2804
40PG66K4	66W	6490	3084

LOW POWER VERSION (20 W/m)

Cod. 3000K	Led	lm	Lmm
40PG18K3	18W	1733	844
40PG24K3	24W	2310	1124
40PG30K3	30W	2888	1404
40PG36K3	36W	3465	1684
40PG42K3	42W	4043	1964
40PG48K3	48W	4621	2244
40PG54K3	54W	5198	2524
40PG60K3	60W	5776	2804
40PG66K3	66W	6354	3084

HIGH POWER VERSION (40 W/m)

Cod. 4000K	Led	lm	Lmm
40PG48K4HP	48W	4719	1124
40PG60K4HP	60W	5900	1404
40PG72K4HP	72W	7080	1684

HIGH POWER VERSION (40 W/m)

Cod. 3000K	Led	lm	Lmm
40PG48K3HP	48W	4621	1124
40PG60K3HP	60W	5776	1404
40PG72K3HP	72W	6931	1684

ACCESSORIES



End caps kit (consider +4mm on the cutting length).

40AA09LED



Linear joint.

40AA11LED



PG screen (UGR<22) in 10m roll to be cut to measure for continuous lines without interruptions.

40PG10000