

STICK 2.0

ID 08

Lighting plays with perspectives thanks to **STICK 2.0**: this cylindrical **profile with internal strip** can be used both horizontally and vertically to create surprising **visual combinations and add a creative touch to living and working environments**. Equipped with an aluminium body with a shockproof diffuser, STICK 2.0 benefits from PG optics to ensure a soft and homogeneous emission with no shadow areas.

☑ Features

- Direct/indirect emission
- UGR<22
- IP 40

💡 Led

- 3000K/4000K
- >125 lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- PG optics for soft and homogeneous emission with no shadow areas

☐ Body

- Aluminum body with a shockproof diffuser for soft emission
- Diecast end caps

☆ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency D
- 5 years warranty

📦 On request


- DALI - code D*
- 2700K - code K27*
- 5000K - code K5*
- Human Centric Lighting*

* Where available



STICK 2.0

Direct/indirect emission with PMMA frosted diffuser UGR<22.
 Fixture complete with 24W/m Strip, power cable and suspensions 3000mm.



❖ Ø 22 ❖



UGR<22

IP 40

Box with driver not included.

Cod. 4000K	Led	lm	Lmm
08DI48PGK4	24+24W	2688	1200
08DI72PGK4	36+36W	4032	1400
08DI96PGK4	48+48W	5376	1900
08DI120PGK4	60+60W	6720	2500

Cod. 3000K	Led	lm	Lmm
08DI48PGK3	24+24W	2472	1200
08DI72PGK3	36+36W	3708	1400
08DI96PGK3	48+48W	4944	1900
08DI120PGK3	60+60W	6180	2500

STICK 2.0 VERTICAL

Direct/indirect emission with PMMA frosted diffuser UGR<22.
 Fixture complete with 24W/m Strip and power cable 3000mm.



❖ Ø 22 ❖



UGR<22

IP 40

Box with driver not included.

Cod. 4000K	Led	lm	Lmm
08DI48PGK4V	24+24W	2688	1200
08DI72PGK4V	36+36W	4032	1400
08DI96PGK4V	48+48W	5376	1900
08DI120PGK4V	60+60W	6720	2500

Cod. 3000K	Led	lm	Lmm
08DI48PGK3V	24+24W	2472	1200
08DI72PGK3V	36+36W	3708	1400
08DI96PGK3V	48+48W	4944	1900
08DI120PGK3V	60+60W	6180	2500

ACCESSORIES



Box with 24V driver
ceiling version.

08BXC

Dali version.

08BXCD



Box with 24V driver
recessed version.

08BXR

Dali version.

08BXRD

CONFIGURATION EXAMPLE

