

STYLO LV is a **miniaturized suspended element with a minimal but elegant design** that can be installed on low voltage 48V tracks. Excellent glare control through a cut-off angle of over thirty degrees.

☑ Features

- Direct emission
- UGR<19
- IP 40

💡 Led

- 3000K/4000K
- >72 lm/W
- CRI>90
- Eye safety: RGO/RGI
- Mac Adams 3
- L80/B10 >50.000h

🕒 Specifications

- 25°-40° polycarbonate lens
- Honeycomb optic
- Diffusing decorative screen

📦 Body

- Die-cast aluminum with epoxy powder coating

🎨 Colors

- White RAL 9003 - code W
- Black RAL 9005 - code BK

☆ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency E
- 5 years warranty

↔ Related products

- LV Track (p. 216)

📦 On request


- DALI - code D*
- Bluetooth - code BT*
- 2700K - code K27*
- 5000K - code K5*

** Where available
For SWITCHDIM
use DIMTDS (p. 38!)*



STYLO LV ZOOM

Lens with adjustable beam from 10°-40°.



IP 40




Power box included and 1500mm cable.

Cod. 4000K	Led	lm	Ømm
88ZM3K4LV	3W	262	31
88ZM5K4LV	5W	560	31

Cod. 3000K	Led	lm	Ømm
88ZM3K3LV	3W	238	31
88ZM5K3LV	5W	510	31

STYLO LV

Polycarbonate lens, 25°-40° beam angle.



IP 40



Power box included and 1500mm cable.

Cod. 4000K	Led	lm	Ømm
88PC5K425LV	5W 25°	360	36
88PC5K440LV	5W 40°	360	36
88PC8K425LV	8W 25°	574	36
88PC8K440LV	8W 40°	574	36

Cod. 3000K	Led	lm	Ømm
88PC5K325LV	5W 25°	318	36
88PC5K340LV	5W 40°	318	36
88PC8K325LV	8W 25°	508	36
88PC8K340LV	8W 40°	508	36

ACCESSORIES



Honeycomb optics for Stylo LV.

88AAND



Decorative frontal ring for Stylo LV.

88AASD