

**TOIK is the wall luminaire with soft and minimal lines.** The perfect solution to illuminate passageways and common spaces, enriching them with the decorative and elegant design of the aluminum body. Available in **different lengths and colors**, in the indirect light version and in the direct/indirect bi-emission version, it provides the **possibility of integrating daylight sensor, emergency light module** and **connections for home automation systems**. TOIK is characterized by its great technological content in an essential and compact body, for a high quality of light and versatility of use.

#### ☑ Features

- Direct/indirect emission
- Indirect emission
- UGR<22
- IP 40

#### 💡 Led

- 3000K/4000K
- >100lm/W
- CRI>90
- Eye safety: RG0/RG1
- Mac Adams 3
- L80/B20 >80.000h

#### 🕒 Specifications

- Built-in driver
- Antistatic satin methacrylate diffuser for homogeneous emission with UGR<22

#### ☐ Body

- Aluminum with epoxy powder coating

#### 🎨 Colors

- White RAL 9003 wrinkled - code W
- Black RAL 9005 wrinkled - code BK

#### ★ Certifications

- CE Conformity
- RETILAP Conformity
- Energy efficiency D
- 5 years warranty

#### ⊕ On request


- DALI - code D
- Bluetooth - code BT\*
- Built-in PIR/Daylight sensor - code S\*
- Emergency 1 hr - code EM
- Emergency 3 hrs - code EM3H\*
- 2700K - code K27\*

\* Where available



# TOIK

Antistatic satin methacrylate diffuser  
UGR<22 with indirect emission.



UGR<22


IP 40

Cod. 4000K	Led	lm	mm
56IN22K4	22W	2389	401
56IN44K4	44W	4770	706
56IN66K4	66W	7150	1011

Cod. 3000K	Led	lm	mm
56IN22K3	22W	2250	401
56IN44K3	44W	4500	706
56IN66K3	66W	6740	1011

# TOIK DOUBLE EMISSION

Antistatic satin methacrylate diffuser  
UGR<22 with direct/indirect emission.



UGR<22

IP 40

Cod. 4000K	Led	lm	mm
56DI28K4	28W	2771	401
56DI56K4	56W	5540	706
56DI84K4	84W	8305	1011

Cod. 3000K	Led	lm	mm
56DI28K3	28W	2650	401
56DI56K3	56W	5300	706
56DI84K3	84W	7940	1011

WALL FLOOR

## TECHNICAL NOTES

### AVAILABLE CONFIGURATIONS

